

APPLICATIONS

Sub-miniature strip to illuminate tight spaces. Ideal for display and shelf lighting. Fixtures may be used individually or linked end to end, without cords.

FEATURES & BENEFITS

- ◆ Sub-miniature housing for tight spaces
- ◆ Fixtures link, without cords, for continuous row mounting
- ◆ Cord, mounting hardware, lamp shipped as a single piece
- ◆ Surface mount brackets, included
- ◆ LED Version: Constant current type driver; 5000K only
- ◆ cETL_{US} Listed



SPECIFICATIONS

Metal construction with acrylic diffuser. Each double insulated fixture is provided with a two prong cord and mounting hardware. Fixtures may be linked (plugged directly, one into another) without a cord for continuous rows. Six inch accessory cord is also available for continuous power around corners.

ORDERING DATA

EXAMPLE: 10M13-LED4E12050

Series	Size/Wattage/Lumens	Driver	Color Temp
10M Sub miniature strip	13LED4 13.5" long, 4 Watts, 380 Lumens 22LED7 22.5" long, 7 Watts, 630 Lumens 23LED8 23.8" long, 8 Watts, 770 Lumens 35LED14 35.6" long, 14 Watts, 1270 Lumens 47LED18 47.4" long, 18 Watts, 1610 Lumens	E120 120VAC	50 5000 K

Each fixture includes cord and plug. 10MLEDJBOX required for hardware.

Accessories

- ◆ 10MLED6JOIN 6" Joiner Cord
- ◆ 10MLED12JOIN 12" Joiner Cord
- ◆ 10MLED18JOIN 18" Joiner Cord
- ◆ 10MLED24JOIN 24" Joiner Cord
- ◆ 10MLEDJBOX J-Box for Hardware



Dimensions (WxLxH)

- ◆ 10M13-LED4E12050 1.06" x 13.5" x .70"
- ◆ 10M22-LED7E12050 1.06" x 22.5" x .70"
- ◆ 10M23-LED8E12050 1.06" x 23.8" x .70"
- ◆ 10M35-LED14E12050 1.06" x 35.6" x .70"
- ◆ 10M47-LED18E12050 1.06" x 47.4" x .70"

Dimensions and specifications subject to change without notice.



CAT#	
JOB NAME	TYPE