

## 15 SERIES

### Corridor Light



Surface mounted corridor fixture with low brightness linear sides. Vandal resistant. For use in indoor applications, such as hallways, bathrooms, aisles and stairwells.

- White opal acrylic wraparound diffuser.
- Screw fastened end caps secures diffuser in place.
- Single or continuous row mounting capability.
- Steel housing with white enamel finish
- UL listed for damp locations

#### CONSTRUCTION

Housing and ends are die-formed cold rolled steel. Finish is high reflectance baked white enamel. Wraparound extruded ribbed white opal diffuser designed for durability and visual comfort. Diffuser is held in place on both ends by the screw fastened end caps. End caps may be removed for continuous row mounting with the use of optional joiner assembly. Mounts over electrical junction box. Mounting holes are provided. Knock-outs are provided for stem mounting.

#### SIZE W x L x H in inches (mm)

- 4.62" x 24.0" x 4.5"
- 4.62" x 36.0" x 4.5"
- 4.62" x 48.0" x 4.5"

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

#### Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

#### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

#### Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

### ORDERING DATA

**EXAMPLE: 15-132LEDL15W840LUN**

Series	# of Lamps	Lamp Type	Lamp Wattage	Color Temp	Brand
15	1	1 Lamp	2 FT	830 3000K	Blank House Brand Lamp (Savegreen)
		17 24 inch T8	LEDL7W 7 Watts 950 Lumens <u>Keystone</u> Brand	835 3500K	
		32 48 inch T8	LEDL9W 9 Watts 1150 Lumens <u>Lunera</u> Brand	840 4000K	LUN Lunera Brand
		32TAN 96 inch T8	LEDL9W 9 Watts 1050 Lumens	850 5000K	KEY Keystone Brand
			4 FT		JAM James Brand**
			LEDL12W 12 Watts 1750 Lumens <u>Keystone</u> Brand		
			LEDL15W 15 Watts 1850 Lumens <u>Lunera</u> Brand		
			LEDL15W 15 Watts 1740 Lumens		
			LEDL18W* 18 Watts 2500 Lumens		

\*Premium Lamp option



Dimensions and specifications subject to change without notice.

800-444-WATT ♦ [www.mobern.com](http://www.mobern.com) ♦

8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE