

APPLICATIONS

Surface mounted corridor fixture with low brightness linear sides. For use in indoor applications, such as hallways, bathrooms, aisles and stairwells.

FEATURES & BENEFITS

- ◆ Available in 4.62"W x 24.0"L x 4.5Dp or 4.62"W x 48.0"L x 4.5Dp
- ◆ White opal acrylic wraparound diffuser
- ◆ Single or continuous row mounting capability
- ◆ Steel housing with white enamel finish
- ◆ Every fixture individually tested
- ◆ _cETL_{US} listed for damp location



SPECIFICATIONS

White opal acrylic wraparound diffuser. Screw fastened end caps secures diffuser in place. Single or continuous row mounting capability. Steel housing with white enamel finish. Housing and ends are die-formed cold rolled steel. Finish is high reflectance baked white enamel. Wraparound extruded ribbed white opal diffuser designed for durability and visual comfort. Diffuser is held in place on both ends by the screw fastened end caps. End caps may be removed for continuous row mounting with the use of optional joiner assembly. Mounts over electrical junction box. Mounting holes are provided. Knock-outs are provided for stem mounting.

ORDERING DATA

EXAMPLE: 15-48LED62DMV40

15	LED	DMV		
Series	Size	Wattage/Lumens	Driver	Color Temp
15 LED Corridor Light	24 24 inch	24 Inch 24 Watts 2400 Lumens	DMV 120-277VAC 0-10V Dimmable	30 3000K
	48 48 inch	31 31 Watts 3100 Lumens		35 3500K
		48 Inch 48 Watts 4800 Lumens		40 4000K
		62 62 Watts 6200 Lumens		50 5000K

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE