

SERIES 158

Wall Mount Bed Light



Commercial grade surface mounted bracket luminaire for use in indoor applications such as nursing homes, hospitals, and other areas requiring a bed light.

- Baffles for up and down light
- Clear acrylic ribbed wraparound lens
- Screw fastened end caps secure diffuser in place
- Individual or continuous row application
- UL listed for damp location

Optional internal divider separates up and down light. Optional front baffle restricts light to up and down only (no front light). Options include, pull chain switches, and convenience outlets.

CONSTRUCTION

Housing and end caps are die-formed from cold rolled steel. Finish is high reflectance baked white enamel. Diffuser is held in place on both ends by screw fastened end caps for a clean look and for easy access to the fixture during maintenance. End caps may be removed for continuous row mounting with the use of optional contour band. Mounts over electrical junction box. Mounting holes are provided.

SIZE W x L x H in inches (mm)

- 2 ft - 5.5/8" x 24 3/8" x 4.5"
- 3 ft - 5.5/8" x 36 3/8" x 4.5"
- 4 ft - 5.5/8" x 48 3/8" x 4.5"

EZ LED

Mobern's EZ LED is the most economical, practical and user friendly series of LED fixtures selling today. EZ LED provides users with high quality light, hassle free maintenance, and greater than 40% energy savings when compared to standard fluorescent options. These fixtures are UL Listed and arrive with the latest UL listed, LED T8 Bypass lamps installed. EZ LED fixtures do not contain a ballast, so you have the ability to change wattage and color temperature at any time by simply swapping out the lamps. Additionally, fixture performance can easily evolve over time simply by installing new LED T8 lamps incorporating advanced T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture? EZ LED solves that by utilizing a self-contained LED lamp that fits into our fixture just like a fluorescent lamp – maintenance is as simple as changing a lamp. EZ LED is simply the Easiest LED solution on the market today!!

Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs at www.mobern.com/EZLEDLamps.
 50,000 Hour Life with 5 Year Warranty
 Aluminum Base and Aluminum Housing
 Color Temperature: 3000K, 3500K, 4000K, 5000K
 G13 Pins (Same as Fluorescent Linear T8 Bipin)
 AC120-277V

Emergency Options:

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.mobern.com/EZLEDemergency.

ORDERING DATA

EXAMPLE: 158-1U2D32BAFLEDL12W840KEY

Series	Uplight / Downlight	Lamp Type	Baffle	Lamp Wattage	Color Temp	Lamp Brand	
158 Wall Mount Bed Light	1U1D One uplight, One downlight	17 24 inch T8	BAF Front Baffle	2 ft.		830 3000K	
		32 48 inch T8		LEDL9W 9 Watts 950 Lumens Keystone	835 3500K		
	1U2D One uplight, Two downlight			LEDL9W 9 Watts 1150 Lumens Lunera	840 4000K	Blank House Brand LUN Lunera Brand KEY Keystone Brand	
				LEDL15W 15 Watts 1700 Lumens	850 5000K		
	2U1D Two uplight, One downlight			4 ft.			
				LEDL12W 12.5 Watts 1750 Lumens Keystone			
	2U2D Two uplight, Two downlight			LEDL15W 15 Watts 1850 Lumens Lunera			
				LEDL15W 15 Watts 1800 Lumens			
					LEDL18W 18 Watts 2100 Lumens		

*Lumens per lamp



Dimensions and specifications subject to change without notice.

CAT#	
JOB NAME	TYPE