

## 159 SERIES

### Wall Mount Bed Light



Specification grade, wall mounted valance luminaire. Designed for restrooms, as a backlight for hospitals, nursing homes and other patient care facilities. Designed as a valance light in public, institutional and sports facilities.

- Technology - Post Powder Paint
- > 90% reflectivity
- Corrosion and scratch resistant
- Smooth edges for easy handling
- Heavy duty construction
- Optional finishes: post powder coated white, post powder coated black
- Lens options: clear prismatic with ribbed front, clear ribbed upright acrylic
- Uplight fixture with divider and upright acrylic optional feature
- UL Listed for damp location

#### CONSTRUCTION

Housing and end are die-formed corrosive resistant code gauge cold rolled steel. Reflective areas are powder coated with high reflectant white paint for improved efficiency. Mounts over electrical junction box. Listed by and bears UL label.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

#### Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

#### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

#### Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

#### ORDERING DATA

#### EXAMPLE: 159232LED12W830LUNWP

159

Series	# Lamps	Lamp Type	Lamp Wattage	Color Temp	Lamp Brand	Options
159	1 1 Lamp	17 24 inch T8	2 ft. LEDL7W 7 Watts 950 Lumens <b>Keystone*</b>	830 3000K	Blank House Brand Lamp (Savegreen) LUN Lunera Brand KEY Keystone Brand JAM James Brand**	WP 6' Whip, 3 Wire
	2 2 Lamps	25 36 inch T8	4 ft. LEDL12W 12.5 Watts 1750 Lumens <b>Keystone*</b>	835 3500K		
	3 3 Lamps	32 48 inch T8	LEDL15W 15 Watts 1850 Lumens <b>Lunera*</b>	840 4000K		
			LEDL15W 15 Watts 1740 Lumens*	850 5000K		
		LEDL18W* 18 Watts 2500 Lumens*			**Special Order	

\*Premium lamp option



Dimensions and specifications subject to change without notice.

◆ 800-444-WATT ◆ [www.mobern.com](http://www.mobern.com) ◆  
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE