


APPLICATIONS

Closed circline utilizes a circular drum design to give designers maximum light output in a classic shape suitable for either ceiling or wall mounts in commercial, residential or hospitality applications.

FEATURES & BENEFITS

- ◆  Technology - Post Powder Paint
- ◆ >90% reflectivity
- ◆ Corrosion and scratch resistant
- ◆ Smooth edges for easy handling
- ◆ Smooth white diffuser provides warm, glare free illumination
- ◆ Optional puff lens and clear acrylic prismatic lens available
- ◆ Three sizes to choose from (11", 14" and 18")
- ◆ Circline or GU based lamping options available
- ◆ Every fixture individually tested
- ◆ UL listed for damp locations



SPECIFICATIONS

Housing is die-formed from cold rolled steel. Finish is high reflectance white with **P3 - Post Powder Paint**. Designers can use this time-proven design with energy efficient circline or compact fluorescent GU based lamps. The diffuser is available in smooth injection molded white acrylic or polycarbonate, or clear prismatic injection molded acrylic and polycarbonate. Listed by and bears **UL** label.

ORDERING DATA

EXAMPLE: 69 11 1 22 ELC

| 69 | | | | | | | | | | | | |
|--------|------|--------------------------|-------------------------------|---------------------------|-------------|--------------|--|---------|----------|-----|---------------------|---|
| Series | Size | Lens Type | | Dimensions & Lamping | | Ballast Type | | Voltage | | | | |
| 69 | 11 | 11" | SW Smooth white (STD-acrylic) | 11x3 | | ELGU | Integrated electronic GU Base (spiral) | Blank | 120 Volt | | | |
| | 14 | 14" | | 1 FC8T9 (22w) | 1 13 W GU24 | | | | | ELC | Electronic circline | MV* Multi-Volt *MV option on PL units only |
| | 18 | 18" | | 2 13W GU24 | 14x3 | | | | | | | |
| | | 22&32W CIRC (FC9 FC12T9) | 2 26W CFL | 3 13W GU24 | 18x3 | | | | | | | |
| | | | | 32&40W CIRC (FC12 FC16T9) | | | | | | | | |

| MODEL CONFIGURATION | A | B |
|---------------------|--------|--------|
| 11 | 3.005" | 11.00" |
| 14 | 3.00" | 14.00" |
| 18 | 3.00" | 18.00" |

Dimensions and specifications subject to change without notice.

