

MOBERN

L I G H T I N G

SERIES 772

Premium Wraparound



Premium grade surface mounted wraparound luminaire with low brightness linear sides. For use in indoor applications where high efficiency, high performance and ease of installation is required. Ideal for retail stores, stairwells, utility areas, schools, offices and public buildings.

- Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- Diffuser self-aligns and hinges from either side for easy maintenance
- Surface, stem or chain mountable
- Single or continuous row mounting capability
- UL listed for damp location

CONSTRUCTION

Housing and ends are die-formed from cold rolled steel. Finish is high reflectance baked white enamel with a reflectance factor exceeding 86%. Diffuser hinges from either side in a lift and shift manner and is self centering. UL listed for damp locations.

SIZE W x L x H in inches

- 2 lamp - 11.25 x 24 x 3.4 (2ft)
- 2 lamp - 11.25 x 48 x 3.4 (4ft)
- 4 lamp - 15.8 x 48 x 3.4 (4ft)
- 4 lamp - 15.8 x 96 x 3.4 (8ft)
- 8 lamp - 15.8 x 96 x 3.4 (8ft)

EZ-LED

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

ORDERING DATA

EXAMPLE: 772-217LEDL15W840WP

772											
Series	# Lamps	Lamp Type	Lamp Wattage		Color Temp	Lamp Brand		Options			
772 Premium Wraparound	2	2 Lamps	17	24 inch T8	2 ft.		830	3000K	Blank House Brand Lamp (Savegreen) LUN Lunera Brand KEY Keystone Brand JAM James Brand**	WP 6' Whip, 3 Wire A69 Wireguard per 4 ft. A144 (2) V-Hook & (2) ft. chain	Consult for other options
	3	3 Lamps	32	48 inch T8	LEDL7W	7 Watts 950 Lumens	835	3500K			
	4	4 Lamps	32TAN	96 inch T8	LEDL9W	9 Watts 1150 Lumens	840	4000K			
					LEDL15W	9 Watts 1050 Lumens	850	5000K			
					4 ft.						
					LEDL12W	12.5 Watts 1750 Lumens					
					LEDL15W	15 Watts 1850 Lumens					
					LEDL15W	15 Watts 1740 Lumens					
					LEDL18W*	18 Watts 2500 Lumens					
					8 ft.						
					LEDL12W	12.5 Watts 1750 Lumens					
					LEDL15W	15 Watts 1850 Lumens					
					LEDL15W	15 Watts 1740 Lumens					
					LEDL18W*	18 Watts 2500 Lumens					

*Premium lamp option



Dimensions and specifications subject to change without notice.

800-444-WATT ♦ www.mobern.com ♦

CAT#

JOB NAME

TYPE