

## 772N SERIES

### Surface Mount Fixture



With 1 lamp in cross-section, the ability to add a reflector and a clear acrylic #8 pattern lens, this wrap around is suitable for a wide variety of applications. A full wireway allows exact lamp spacing and uniform light distribution.

#### CONSTRUCTION

Housing is a baked white enamel cold rolled steel body and ends. Wiring knockouts are provided on back and end of housing. Reflector snaps into place, no tools required. Lens is held with lift and shift method. Premium, full specular reflectors are available as an option to increase efficiency or modify lighting distribution.

#### SIZE W x L x H in inches (mm)

5.625" x 48" x 3.187"

#### EZ LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. EZ LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, EZ LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

#### Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs at [www.mobern.com/EZLEDLamps](http://www.mobern.com/EZLEDLamps).

50,000 Hour Life with 5 Year Warranty  
 Aluminum Base and Aluminum Housing with Glass Cover  
 Operating Temperature: - 20°C to 50°C  
 Color Temperature: 3500K, 4000K, 5000K  
 G13 Pins (Same as Fluorescent Linear T8 Bipin)  
 AC100 – 277V

#### Emergency Options:

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at [www.mobern.com/EZLEDemergency](http://www.mobern.com/EZLEDemergency).

ITEM NO.	DESCRIPTION
772N-117LEDL15W840	5" x 24" 1700 Lumen 1 Light Wraparound w/1x15W LED T8 4000K Lamps Included
772N-132LEDL15W840LUN	5" x 48" 1850 Lumen 1 Light Wraparound w/1x15W LED T8 4000K Lamps Included

Change 40 to 35 etc. for different Kelvin. For 13W 2 ft lamp, change 15W to 13W

Mobern reserves the right to substitute our own UL DLC listed tubes.

