

## 772N SERIES

### Surface Mount Fixture



With 1 lamp in cross-section, the ability to add a reflector and a clear acrylic #8 pattern lens, this wrap around is suitable for a wide variety of applications. A full wireway allows exact lamp spacing and uniform light distribution.

#### CONSTRUCTION

Housing is a baked white enamel cold rolled steel body and ends. Wiring knockouts are provided on back and end of housing. Reflector snaps into place, no tools required. Lens is held with lift and shift method. Premium, full specular reflectors are available as an option to increase efficiency or modify lighting distribution.

#### SIZE W x L x H in inches

5.625 x 24 x 3.187

5.625 x 48 x 3.187

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

#### Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

#### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

#### Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

### ORDERING DATA

**EXAMPLE: 772N-117LEDL9W830WP**

772N

Series	# Lamps	Lamp Type	Lamp Wattage	Color Temp	Lamp Brand	Options*
772N Surface Mount Fixture	1 1 Lamp	17 24 inch T8	<b>2 ft.</b> LEDL7W 7 Watts 950 Lumens <b>Keystone</b>	830 3000K	Blank House Brand Lamp (Savegreen) LUN Lunera Brand KEY Keystone Brand JAM James Brand**	WP 6' Whip, 3 Wire
	2 2 Lamp	32 48 inch T8	LEDL9W 9 Watts 1150 Lumens <b>Lunera</b> LEDL9W 9 Watts 1050 Lumens	835 3500K 840 4000K 850 5000K		
			<b>4 ft.</b> LEDL12W 12.5 Watts 1750 Lumens <b>Keystone</b> LEDL15W 15 Watts 1850 Lumens <b>Lunera</b> LEDL15W 15 Watts 1740 Lumens LEDL18W* 18 Watts 2500 Lumens			

\*Premium lamp option

\*\*Special Order



Dimensions and specifications subject to change without notice.

◆ 800-444-WATT ◆

◆ [www.mobern.com](http://www.mobern.com) ◆

CAT#

JOB NAME

TYPE