

FEATURES & BENEFITS

- ◆ Surface mounts to existing junction box or new construction with two screws
- ◆ Slim close-to-ceiling LED arrays providing 10W with 660/720 lumens and 15W with 850/1000 lumens at 3000K color temperature
- ◆ CTCS and CTCR Series dims to 10% with standard dimmers*
- ◆ ^CETL_{US} listed for wet locations
- ◆ White or brushed nickel finish

* Triac Based (forward phase control or leading edge dimmers)



ORDERING DATA

EXAMPLE: CTCS5LED10D120WH30

Series	Size	LED Gear	Wattage	Driver	Finish	Color Temp
CTCS	5 5 inches	LED	10 10 Watts*	D120	WH	30 3000K
Square	7 7 inches		15 15 Watts**	120V Triac Dimmable	BN	
CTCR						
Round						

*Only available in 5 inch
**Only available in 7 inch

DIMENSIONS

Dimensions In Inches	
CTCR5LED10	5.5"D x 0.625"H, 660 Lumens
CTCR7LED15	7.0"D x 0.625"H, 850 Lumens
CTCS5LED10	6.28"L x 0.625"H, 720 Lumens
CTCS7LED15	8.0"L x 0.625"H, 1000 Lumens

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#	
JOB NAME	TYPE