

APPLICATIONS

The DLV LED Modern Louvered Industrial Strip fixture can change the look of any space. It makes a bold statement with the semi specular parabolic louver. It's industrial look provides a modern aesthetic with a blast of light that's glare free. Suspended on cables, the hanging Powder Coat Finish fixtures look stylish in any setting. Illuminate any workspace. It is ideal for corridors, lobbies and other office areas.

FEATURES & BENEFITS

- ◆ SIZE 8.0W x 49.0L or 98.0L x 6.5H
- ◆ LED drive technology - Constant current
- ◆ Surface, ceiling or pendant hung
- ◆ ETL Listed
- ◆ Long life LED system
- ◆ Double the life of fluorescent technology
- ◆ 5 year warranty



SPECIFICATIONS

The Housing is Die-formed cold rolled steel body with heavy duty construction. Mates with Parabolic louver which is a silver anodized with optional slots on the side of louver. End caps complete the finished louvered look.

ORDERING DATA

EXAMPLE: DLV48LED48DMVWH40WH

DLV		LED		Driver		Finish		Cord/Canopy Finish	
Series	Size	Gear							
DLV Louvered Industrial Strip	48 48 inches 96 96 inches	LED		DMV 120-277 VAC 0-10V Dimmable	WH White BK Black BZ Bronze GV Galvanized Steel SI Silver	WH White BK Black BZ Bronze GV Galvanized Steel SI Silver		WH White BK Black BKWH Black cord white canopy	
	Wattage/Lumens								
		48"							
	24	24 Watts	2400 Lumens						
	48	48 Watts	4800 Lumens						
	57	57 Watts	5400 Lumens						
	72	72 Watts	8200 Lumens						
	144	144 Watts	16450 Lumens						
		96"							
	48	48 Watts	5650 Lumens						
	97	97 Watts	11300 Lumens						
	114	114 Watts	12800 Lumens						
						Color Temp			
						30 3000K			
						35 3500K			
						40 4000K			
						50 5000K			
								Options	
								HC301	Cable kit with 4' cable & power feed/0-10V dimming
								HC3015W	Cable kit with a 4' cable & power feed/0-10V dimming (5 wire)
								HC302	Cable kit with 12' Cable and Power Feed/0-10V dimming
								HC3025W	Cable kit with a 12' Cable and power feed/0-10V dimming (5 wire)
								2SCS24WH	Two stem kits with 24" stem, canopy, and mounting hardware for a 4' fixture

*See chart below for whip & cord ordering options

*Cord & Whip Ordering Chart (Add to End of Fixture Part Number)

Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip	(Blank) 3 Wire	(Blank) 6 feet	(Blank) No Plug	BK - Black	(Blank) 120-277V	15 - 15 Amps
CS - Cordset	4 - 4 Wire	8 - 8 feet	P* - Standard Plug	WH - White	120 - 120V	20 - 20 Amps
	5 - 5 Wire	10 - 10 feet	TL* - Twist Lock		277 - 277V	
	6 - 6 Wire	12 - 12 feet			347 - 347V	
		15 - 15 feet			480 - 480V	

Dimensions and specifications subject to change without notice.

