

APPLICATIONS

A direct/indirect lighting fixture that makes a bold statement by complementing design elements such as stone, metal, brick and glass. Industrial look provides a modern aesthetic. Available standard in white finish with matte silver anodized parabolic louver. Mounts with cable kit.

FEATURES & BENEFITS

- ◆ Available standard in white finish or powder coated black
- ◆ Mounts with cable kit
- ◆ Size: 6.0W x 48.0L x 5.25H
- ◆ 5 year warranty

SPECIFICATIONS

Die-formed cold rolled steel body with heavy duty construction. Fixtures can be surface mounted to the ceiling or pendant hung by stem or cable. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting.



ORDERING DATA

EXAMPLE: DLV6132MVWHEM-HC301WH

DLV6

Series	Lamp Type	Ballast	Finish	Options	Cord/Canopy Finish
DLV6 Louvered Industrial Strip	17 24" T8 21 34" T5 24 22" T5HO 25 36" T8 28 46" T5 32 48" T8 39 36" T5HO 54 46" T5HO	MV 120-277VAC 120 120V 277 277V	WH White BK Black BZ Bronze GV Galvanized Steel SI Silver	EM Emergency Battery Pack 10W ~ 1300 Lumens EM5 Emergency Battery Pack 5W ~ 650 Lumens EM7 Emergency Battery Pack 7W ~ 900 Lumens LED Wired 1 end hot for T8 LED tubes* LED2E Wired 2 ends hot for T8 LED tubes* <small>*Assembled with no ballast, made for UL listed, self ballasted retrofit LED lamps</small>	WH White BK Black BKWH Black cord/white canopy
# of Lamps 1 1 lamp 2 2 lamps					
				Optional/Cable Kit	
				HC301 Cable kit with 4' cable & power feed/0-10V dimming	
				HC3015W Cable kit with a 4' cable & power feed/0-10V dimming (5 wire)	
				HC302 Cable kit with 12' Cable and Power Feed/0-10V dimming	
				HC3025W Cable kit with a 12' Cable and power feed/0-10V dimming (5 wire)	
				2SCS24WH Two stem kits with 24" stem, canopy, and mounting hardware for a 4' fixture	

**See chart below for whip & cord ordering options

**Cord & Whip Ordering Chart (Add to End of Fixture Part Number)						
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip	(Blank) 3 Wire	(Blank) 6 feet	(Blank) No Plug	BK - Black	(Blank) 120-277V	15 - 15 Amps
CS - Cordset	4 - 4 Wire	8 - 8 feet	P* - Standard Plug	WH - White	120 - 120V	20 - 20 Amps
	5 - 5 Wire	10 - 10 feet	TL* - Twist Lock		277 - 277V	
	6 - 6 Wire	12 - 12 feet			347 - 347V	
		15 - 15 feet			480 - 480V	



Dimensions and specifications subject to change without notice.

CAT#	
JOB NAME	
TYPE	