

SERIES L44

4x4 Linear Pendant, Surface and Wall



The linear 4x4 pendant or surface mounted fixture is for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas. The 4x4 Series fixtures can be installed individually or in group patterns.

- Fixtures can be surface mounted to the ceiling or pendant hung by stem, cable or wall mounted
- Accepts various lenses or louvers
- 6' and 8' units have a steel mullion to join two individual diffusers
- Optional welded light-leak hinges are available on ends
- Alignment brackets are available for continuous row mounting
- UL listed for damp location

CONSTRUCTION

Die-formed and welded cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide some uplight for ceiling illumination.

SIZE W x L x H in inches (mm)

4"W x 4"H x fixture length

EZ LED

Mobern's EZ LED is the most economical, practical and user friendly series of LED fixtures selling today. EZ LED provides users with high quality light, hassle free maintenance, and greater than 40% energy savings when compared to standard fluorescent options. These fixtures are UL Listed and arrive with the latest UL listed, LED T8 Bypass lamps installed. EZ LED fixtures do not contain a ballast, so you have the ability to change wattage and color temperature at any time by simply swapping out the lamps. Additionally, fixture performance can easily evolve over time simply by installing new LED T8 lamps incorporating advanced T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture? EZ LED solves that by utilizing a self-contained LED lamp that fits into our fixture just like a fluorescent lamp – maintenance is as simple as changing a lamp. EZ LED is simply the Easiest LED solution on the market today!!

Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs at www.mobern.com/EZLEDLamps.
 50,000 Hour Life with 5 Year Warranty
 Aluminum Base and Aluminum Housing
 Color Temperature: 3000K, 3500K, 4000K, 5000K
 G13 Pins (Same as Fluorescent Linear T8 Bipin)
 AC120-277V

Emergency Options:

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.mobern.com/EZLEDemergency.

ORDERING DATA

EXAMPLE: L44RMW-232LEDL15W840LUN

L44

Series	Reflector	Lens Options	# Lamps	Lamp Type	Finish	Color Temp	Lamp Brand
L44	Blank Standard WW Wall wash	MW Smooth white .100 thick lens standard	1 1 Lamp 2 2 Lamps	17 24 inch T8 25 36 inch T8 25TAN 72 inch T8 - 2-36"	BLANK For Recess WH White BK Black SL Silver IN Iron BZ Bronze	830 3000K 835 3500K 840 4000K 850 5000K	Blank House Brand LUN Lunera Brand KEY Keystone Brand
Mounting		S5 Specular parabolic louver 1/2"x 1/2"x3/8"					
R	Regular recess lay-in	SF Snap-in frosted lens					
RF	Recessed with flange*	LV Baffled louver					
RR	Recessed for dry wall 1/2"	A Prismatic acrylic #12 pattern					
S	Surface/pendant (direct only)						
SI	Surface/pendant (indirect only)						
SDI	Surface/pendant direct w/indirect slots						
WI	Wall mount indirect only						
WDI	Wall mount direct w/indirect slots						
W	Wall mount direct only						
				Lamp Wattage		OPTIONS	
				2 FT		HC301WH Cable kit with 4' CABLE + power feed cable incl. with white canopy	
				3 FT		HC302WH Cable kit with 12' CABLE +power feed cable incl. with white canopy	
				4 FT		PLUG IN OPTIONS FOR CONTINUOUS RUNS	
				LEDL7W 7 WATTS 950 LUMENS KEYSTONE		PI1 3 wire harness White, black, and green	
				LEDL9W 9 WATTS 1150 LUMENS LUNERA		PI2 4 wire harness White, Black, Green, and Blue for battery backup	
				LEDL15W 15 WATTS 1700 LUMENS		PI3D 5 wire harness White, Black, Green, Violet, and Grey - For Dimming	
				LEDL12W 12 WATT 1250 LUMENS KEYSTONE			
				LEDL12W 12.5 WATTS 1750 LUMENS KEYSTONE			
				LEDL15W 15 WATTS 1850 LUMENS LUNERA			
				LEDL15W 15 WATTS 1800 LUMENS			
				LEDL18W 18 WATTS 2100 LUMENS			

*RF for sheetrock installation

*Lumens per lamp

Dimensions and specifications subject to change without notice.



800-444-WATT www.mobern.com
 8200 Staton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE