

MOBERN

L I G H T I N G

SERIES L44

4x4 Linear Pendant, Surface and Wall



The linear 4x4 pendant or surface mounted fixture is for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas. The 4x4 Series fixtures can be installed individually or in group patterns.

- Fixtures can be surface mounted to the ceiling or pendant hung by stem, cable or wall mounted
- Accepts various lenses or louvers
- 6' and 8' units have a steel mullion to join two individual diffusers
- Optional welded light-leak hinges are available on ends
- Alignment brackets are available for continuous row mounting
- UL listed for damp location

CONSTRUCTION

Die-formed and welded cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide some uplight for ceiling illumination.

SIZE W x L x H in inches (mm)

4"W x 4"H x fixture length

EZ-LED

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

ORDERING DATA

EXAMPLE: L44RMW-232LEDL15W840LUN

L44

Series	Reflector	Lens Options	# Lamps	Lamp Type	Finish	Color Temp	Lamp Brand
L44	Blank Standard WW Wall wash	MW Smooth white .100 thick lens S5 Specular parabolic louver 1/2"x 1/2"x3/8"	1 1 Lamp 2 2 Lamps	17 24 inch T8 25 36 inch T8 25TAN 72 inch T8 - 2-36"	BLANK For Recess WH White BK Black SL Silver IN Iron BZ Bronze	830 3000K 835 3500K 840 4000K 850 5000K	Blank House Brand Lamp (Savegreen) LUN Lunera Brand KEY Keystone Brand JAM James Brand** **Special Order
Mounting				Lamp Wattage		Options	
R	Regular recess lay-in	SF Snap-in frosted lens		2 FT		HC301WH	Cable kit with 4' CABLE + power feed cable incl. with white canopy
RF	Recessed with flange*	LV Baffled louver		3 FT		HC302WH	Cable kit with 12' CABLE +power feed cable incl. with white canopy
RR	Recessed for dry wall 1/2"	A Prismatic acrylic #12 pattern		4 FT		PLUG IN OPTIONS FOR CONTINUOUS RUNS	
S	Surface/pendant (direct only)		LEDL7W 7 WATTS 950 LUMENS <u>KEYSTONE</u> LEDL9W 9 WATTS 1150 LUMENS <u>LUNERA</u> LEDL15W 9 WATTS 1050 LUMENS		PI1	3 wire harness White, black, and green	
SI	Surface/pendant (indirect only)		LEDL12W 12 WATT 1250 LUMENS <u>KEYSTONE</u>		PI2	4 wire harness White, Black, Green, and Blue for battery backup	
SDI	Surface/pendant direct w/indirect slots)		LEDL12W 12.5 WATTS 1750 LUMENS <u>KEYSTONE</u> LEDL15W 15 WATTS 1850 LUMENS <u>LUNERA</u> LEDL15W 15 Watts 1740 Lumens LEDL18W* 18 Watts 2500 Lumens		PI3D	5 wire harness White, Black, Green, Violet, and Grey - For Dimming	
WI	Wall mount indirect only						
WDI	Wall mount direct w/indirect slots						
W	Wall mount direct only						

*RF for sheetrock installation

*Premium lamp option



Dimensions and specifications subject to change without notice.



800-444-WATT www.mobern.com
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE