

### APPLICATIONS

The linear 4x4 pendant or surface mounted fixture is for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas. The 4x4 Series fixtures can be installed individually or in group patterns.

### FEATURES & BENEFITS

- ◆ 2 or 4 lamp positions
- ◆ Fixtures can be surface mounted to the ceiling, recessed in ceiling or pendant hung by stem or cable
- ◆ Accepts various lenses or louvers
- ◆ 8' units have a steel mullion to join two individual diffusers
- ◆ Consult factory for other lengths
- ◆ Optional welded light-leak flanges are available on ends
- ◆ Every fixture is individually tested
- ◆ **UL** listed for damp location



### SPECIFICATIONS

Die-formed and welded 22-gauge cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide approximately 12% uplight for ceiling illumination.

### ORDERING DATA

EXAMPLE: L44RSW228MVWH

Series	Mounting	Direct/Indirect	# Lamps	Lamp Type	Ballast	Finish
L44	R Regular Recess Lay-in	Blank Recessed Surface or Wall Direct only	1	14 24" T5	MV 120-277VAC	WH White
Reflector	RF Recessed with Flange*	I Indirect only	2	17 24" T8	DMV 0-10V Dimming 120-277VAC Multivolt	SL Silver
Blank Standard	RR Recessed for Dry Wall 1/2"	DI Direct w/Indirect Slots	Per cross section	21 36" T5		BK Black
WW Wall wash	S Surface/Pendant Direct only			24 24" T5HO	R120 Residential 120V Ballast	BZ Bronze
	W Wall Mount Direct only			24TAN 2-24" TAN T5HO	PMV Program Start Multivolt	IN Iron
	* RF for sheetrock installation			25 36" T8	LED** Wired 1 end hot for T8 LED lamps	
				25TAN 2-36" TAN T8	LED2E** Wired 2 ends hot for T8 LED lamps	
				28 46" T5		
				28TAN 2-46" TAN T5		
				32 48" T8		
				32TAN 2-48" TAN T8		
				39 36" T5HO		
				54 46" T5HO		
				54TAN 2-46" TAN T5HO		




Notes:  
Example: SDI Surface/Pendant Direct w/Indirect Slots  
WI Wall Mount Indirect only

\*\* Assembled with no ballast, made for UL Listed, self ballasted retrofit LED lamps. Lamps not included

Options	Plug In Options for Continuous Runs
B1 T8/T5 1L500 lumen battery backup	PI1 3 wire harness, including white, black and green
B2 T8/T5 1L/2L 700 lumen battery backup	PI2 4 wire harness, including white, black, green and blue for emergency battery backup
B3 T8/T5 1L/2L 1400 lumen battery backup	PI3D 5 wire harness, including white, black, green violet and grey for dimming
B51 T5HO 1L 500 lumen battery backup	
B52 T5HO 1L 800 lumen battery backup	
B53 T5HO 1L 1300 lumen battery backup	
L841 Lamps installed 841K	
L835 Lamps installed 835K	
HC301WH Cable kit w/4' cable + power feed cable incl.w/white canopy	
HC302WH Cable kit w/12' cable + power feed cable incl.w/white canopy	

Dimensions and specifications subject to change without notice.





For Wall Wash version,  
add "WW" after L44

### OPTIONS

- HC301WH Cable kit with 4 cable + power feed cable included with white canopy
- HC302WH Cable kit with 12 cable + power feed cable included with white canopy
- Stem kits sold separately

### NOTES

- [1] Consult Factory for additional lamps, ballasts, finishes, and options.
- [2] Consult factory for recessed version

Dimensions and specifications subject to change without notice.

