

L66 SERIES

Recessed, Surface, Wall, or Pendant Mount



A linear 6x6 surface mounted fixture for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas, 6x6 fixtures can be installed individually or in group patterns. UL listed for damp locations.

CONSTRUCTION

Die-formed and welded cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide approximately 12% uplight for ceiling illumination. Fixtures can be surface mounted to the ceiling, pendant hung by stem, cable, or wall mounted. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting. Fixtures can be mounted flush against the wall or hung with wall brackets measuring 4 1/2" square by 1" deep. Two brackets are used on 2, 3 and 4 foot fixtures and 2 or 3 brackets for 6 and 8 foot fixtures as required.

SIZE W x L x H in inches (mm)

- 2ft - 6" x 24" x 6"
- 4ft - 6" x 48" x 6"
- 8ft - 6" x 96" x 6"

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

ORDERING DATA

EXAMPLE: L66RMW-232LEDL15W840LUN

L66

Series	Reflector	Lens Options	# Lamps	Lamp Type	Finish	Color Temp	Lamp Brand
L66	Blank Standard WW Wall wash	MW Smooth white .100 thick lens standard	1 1 Lamp 2 2 Lamps	17 24 inch T8 25 36 inch T8 25TAN 72 inch T8 - 2-36"	BLANK For Recess WH White BK Black SL Silver IN Iron BZ Bronze	830 3000K 835 3500K 840 4000K 850 5000K	Blank House Brand Lamp (Savegreen) LUN Lunera Brand KEY Keystone Brand JAM James Brand** **Special Order
Mounting		S5 Specular parabolic louver 1/2"x 1/2"x3/8"		32 48 inch T8 32TAN 96 inch T8 - 2-48			
R	Regular recess lay-in	SF Snap-in frosted lens		Lamp Wattage			
RF	Recessed with flange*	LV Baffled louver		2 FT			
RR	Recessed for dry wall 1/2"	A Prismatic acrylic #12 pattern		LEDL7W 7 WATTS 950 LUMENS	KEYSTONE		
S	Surface/pendant (direct only)			LEDL9W 9 WATTS 1150 LUMENS	LUNERA		
SI	Surface/pendant (indirect only)			LEDL9W 9 WATTS 1050 Lumens			
SDI	Surface/pendant direct w/indirect slots)			3 FT			
WI	Wall mount indirect only			LEDL12W 12 WATT 1250 LUMENS	KEYSTONE		
WDI	Wall mount direct w/indirect slots			4 FT			
W	Wall mount direct only			LEDL12W 12.5 WATTS 1750 LUMENS	KEYSTONE		
				LEDL15W 15 WATTS 1850 LUMENS	LUNERA		
				LEDL15W 15 Watts 1740 Lumens			
				LEDL18W* 18 Watts 2500 Lumens			

OPTIONS

- HC301WH Cable kit with 4' CABLE + power feed cable incl. with white canopy
- HC302WH Cable kit with 12' CABLE + power feed cable incl. with white canopy

PLUG IN OPTIONS FOR CONTINUOUS RUNS

- PI1 3 wire harness
White, black, and green
- PI2 4 wire harness
White, Black, Green, and Blue for battery backup
- PI3D 5 wire harness
White, Black, Green, Violet, and Grey - For Dimming

*RF for sheetrock installation

*Premium lamp option

Dimensions and specifications subject to change without notice.



800-444-WATT ♦ www.mobern.com ♦

8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE