

## L66 SERIES

Recessed, Surface, Wall, or Pendant Mount



A linear 6x6 surface mounted fixture for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas, 6x6 fixtures can be installed individually or in group patterns. UL listed for damp locations.

### CONSTRUCTION

Die-formed and welded cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide approximately 12% uplight for ceiling illumination. Fixtures can be surface mounted to the ceiling, pendant hung by stem, cable, or wall mounted. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting. Fixtures can be mounted flush against the wall or hung with wall brackets measuring 4 1/2" square by 1" deep. Two brackets are used on 2, 3 and 4 foot fixtures and 2 or 3 brackets for 6 and 8 foot fixtures as required.

### SIZE W x L x H in inches (mm)

- 2ft - 6" x 24" x 6"
- 4ft - 6" x 48" x 6"
- 8ft - 6" x 96" x 6"

### EZ LED

Mobern's EZ LED is the most economical, practical and user friendly series of LED fixtures selling today. EZ LED provides users with high quality light, hassle free maintenance, and greater than 40% energy savings when compared to standard fluorescent options. These fixtures are UL Listed and arrive with the latest UL listed, LED T8 Bypass lamps installed. EZ LED fixtures do not contain a ballast, so you have the ability to change wattage and color temperature at any time by simply swapping out the lamps. Additionally, fixture performance can easily evolve over time simply by installing new LED T8 lamps incorporating advanced T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture? EZ LED solves that by utilizing a self-contained LED lamp that fits into our fixture just like a fluorescent lamp – maintenance is as simple as changing a lamp. EZ LED is simply the Easiest LED solution on the market today!!

### Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs at [www.mobern.com/EZLEDLamps](http://www.mobern.com/EZLEDLamps).  
50,000 Hour Life with 5 Year Warranty  
Aluminum Base and Aluminum Housing  
Color Temperature: 3000K, 3500K, 4000K, 5000K  
G13 Pins (Same as Fluorescent Linear T8 Bipin)  
AC120-277V

### Emergency Options:

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at [www.mobern.com/EZLEDEmergency](http://www.mobern.com/EZLEDEmergency).

### ORDERING DATA

### EXAMPLE: L66RMW-232LEDL15W840LUN

L66

Series	Reflector	Mounting	Lens Options	# Lamps	Lamp Type	Finish	Color Temp	Lamp Brand	
L66	Blank Standard WW Wall wash	R Regular recess lay-in RF Recessed with flange* RR Recessed for dry wall 1/2" S Surface/pendant (direct only) SI Surface/pendant (indirect only) SDI Surface/pendant direct w/indirect slots) WI Wall mount indirect only WDI Wall mount direct w/indirect slots W Wall mount direct only	MW Smooth white .100 thick lens S5 Specular parabolic louver 1/2"x 1/2"x3/8" SF Snap-in frosted lens LV Baffled louver A Prismatic acrylic #12 pattern	1 1 Lamp 2 2 Lamps	17 24 inch T8 25 36 inch T8 25TAN 72 inch T8 - 2-36" 32 48 inch T8 32TAN 96 inch T8 - 2-48"	BLANK For Recess WH White BK Black SL Silver IN Iron BZ Bronze	830 3000K 835 3500K 840 4000K 850 5000K	Blank House Brand LUN Lunera Brand KEY Keystone Brand	
					<b>Lamp Wattage</b> <b>2 FT</b> LEDL7W 7 WATTS 950 LUMENS <b>KEYSTONE</b> LEDL9W 9 WATTS 1150 LUMENS <b>LUNERA</b> LEDL15W 15 WATTS 1700 LUMENS <b>3 FT</b> LEDL12W 12 WATT 1250 LUMENS <b>KEYSTONE</b> <b>4 FT</b> LEDL12W 12.5 WATTS 1750 LUMENS <b>KEYSTONE</b> LEDL15W 15 WATTS 1850 LUMENS <b>LUNERA</b> LEDL15W 15 WATTS 1800 LUMENS LEDL18W 18 WATTS 2100 LUMENS		<b>OPTIONS</b> HC301WH Cable kit with 4' CABLE + power feed cable incl. with white canopy HC302WH Cable kit with 12' CABLE + power feed cable incl. with white canopy <b>PLUG IN OPTIONS FOR CONTINUOUS RUNS</b> PI1 3 wire harness White, black, and green PI2 4 wire harness White, Black, Green, and Blue for battery backup PI3D 5 wire harness White, Black, Green, Violet, and Grey - For Dimming		

\*RF for sheetrock installation

\*Lumens per lamp

Dimensions and specifications subject to change without notice.



800-444-WATT ♦ [www.mobern.com](http://www.mobern.com) ♦  
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE