

APPLICATIONS

Full body micro silhouette makes a bold statement with a minimal design in post painted powder coated flat white polyester finish (consult factory for other finishes). Scaled to the LED module the matte white diffuser surrounds the LEDs for a soft lighting. Fixture can be surface mounted on the wall or ceiling or pendant mounted with specially engineered cable mounting kit.

FEATURES & BENEFITS

- ◆ Fully assembled housing is formed and welded 22 gauge steel chemically treated to resist corrosion and enhance paint adhesion
- ◆ Can be mounted individually or in continuous row
- ◆ Available with smooth frosted lens
- ◆ Knockouts on back accept standard electrical fittings (by others)
- ◆ Optional occupancy sensors, whips, fuses and cord set
- ◆ Optional sensor is self-contained, interchangeable and push-button programmable
- ◆ Surface or pendant mounted horizontally or vertically

SIZE:
2.83"H x 2.36"W x 23.60"L
2.83"H x 2.36"W x 47.25"L
2.83"H x 2.36"W x 94.43"L



Optional:
Add SS to the end of the part number for Occupancy Sensor

ORDERING DATA

EXAMPLE: LD23-24LED14FRDMVWH30

LD23		LED		FR		Driver		Finish		Color Temp		Configuration	
Series	Length	Gear	Wattage & Lumens		Lens	Driver		Finish		Color Temp		Configuration	
LD23	24 48 96	23.6" 47.15" 94.43"	LED	14 20	2 FT 14 Watts 1400 Lumens 2000 Lumens	FR Frosted	DMV 120-277 VAC 0-10V Dimmable	WH White BK Black BN Brushed Nickel OR Orange IN Iron BZ Bronze	30 3000K 35 3500K 40 4000K 50 5000K	Options		Blank Individual -B Beginner Run -E Ender Run -J Joiner	
				28 31 40 45	4 FT 28 Watts 2800 Lumens 31 Watts 3200 Lumens 40 Watts 4000 Lumens 45 Watts 4500 Lumens		*Consult for step dimming			SS Step Dim Sensor 50% Dim Level OSD Integral Daylight Occ sensor			
				56 62 80	8 FT 56 Watts 5600 Lumens 62 Watts 6200 Lumens 80 Watts 8000 Lumens					HC401WH Cable kit with 4' cable & power feed 0-10V Dimming Cable incl. w/white canopy HC401WH-5W Cable kit with 4' cable & power feed 0-10V Dimming Cable incl. w/white canopy (5 wire) HC402WH Cable kit with 12' cable & power feed 0-10V Dimming Cable incl. w/white canopy HC402WH-5W Cable kit with 12' cable & power feed 0-10V Dimming Cable incl. w/white canopy (5 wire) 2SCS24WH Two stem kits w/24" stem, canopy & mounting hardware for 4' fixture			

DIMENSIONS



Options & Accessories:

Consult Buyers Guide or factory

*Consult factory for more options

- P11 3 wire harness, including white, black and green
- P12 4 wire harness, including white, black, green and blue for emergency backup
- P13D 5 wire harness, including white, black, green, violet and gray

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆
8200 Stayton Dr., Ste. 500, Jessup MD 20794

CAT#	
JOB NAME	
TYPE	