

APPLICATIONS

Mobern introduces LED low profile rectilinear lighting that can be pendant or wall mounted individually. Ideal for general lighting applications in both commercial and residential applications for circulation spaces, high impact areas and kitchen islands and home offices. The versatility and clean styling makes this an ideal choice in many applications.

FEATURES & BENEFITS

- ◆ Size: (W x L x H in inches)
4ft. - 7.60" x 48.0" x 1.9"
8ft. - 7.60" x 96.0" x 1.9"
- ◆ Mount with 4' adjustable cable and power feed (2 for 4' unit or 8' unit, included) Consult factory for longer cables.



Two Lumen Packages
Available in Standard output and High output lumen packages

ORDERING DATA

EXAMPLE: LLPMW48LED24DMVWH30

LL		LED		Driver		Color Temp		Cable Kit			
Series	LL	Length	48 48" 96 96"	Gear	LED	DMV	0-10V Dimming 120-277V Multi-volt	30	3000K	(blank)	4ft Cable kit w/ 3 wire white cord & cable
Mounting	P Low Profile Pendant W Low Profile Wall Mount	Lens	MW White Lens FR Frosted Lens					35	3500K	HC402WH	12 ft cable kit w/ 3 wire white cord & cable
		LED Module Distribution				Wattage & Lumens		40	4000K	HC401WH-5W	4 ft cable kit w/ 5 wire white cord & cable
		(blank)	Downlight only	24	24 Watts / 2400 Lumens	4 Ft. Up or Down Only		50	5000K	HC402WH-5W	12 ft cable kit w/ 5 wire white cord & cable
		U	Uplight only	48	48 Watts / 4800 Lumens	4 Ft. Uplight & Downlight					
		1U2D	1/3 Uplight 2/3 Downlight	36	36 Watts / 3600 Lumens	8 Ft. Up or Down Only					
		2U1D	2/3 uplight 1/3 downlight	54	54 Watts / 5400 Lumens	8 Ft. Uplight & Downlight					
				48	48 Watts / 4800 Lumens						
				96	96 Watts / 9600 Lumens						
				72	72 Watts / 7200 Lumens						
				108	108 Watts / 10800 Lumens						
										Options*	
										EM	10 Watt 1200 Lumens** Battery Backup
										EM5	5 Watt 600 Lumens** Battery Backup
										EM7	7 Watt 840 Lumens** Battery Backup

*Consult for more options

Dimensions and specifications subject to change without notice.

