

APPLICATIONS

Premium grade, designer, shallow, surface mounted wraparound luminaire. For use in indoor application where aesthetics and quality are important, such as kitchens, recreation rooms, nursing homes, retail stores and office areas. Regressed housing provides a floating appearance.

SIZE:

9.75"W x 50.0"L x 3.375"H
13.75"W x 50.0"L x 3.375"H



FEATURES & BENEFITS

- ◆ Every fixture is individually tested
- ◆ ETL_{us} Listed

SPECIFICATIONS

Die formed and spot welded, 22 gauge cold rolled steel housing. Spot welded for rigidity and clean appearance. Ballast cover snaps into place eliminating the need for tools when accessing the ballast. Diffuser hinges from either side in a lift and shift manner and is self centering.

Mounting: Mounts over electrical junction box. Offset mounting pads which keeps luminaire level and slightly off of mounting surface, are formed within the housing. Mounting holes are provided within offset to prevent distortion of housing when tightening mounting fasteners.

Diffuser: Specially formed plastic diffuser produces flawless light source with even illumination on all sides and no distracting spots. Invisible hanging clips permit removal of lens from either side

ORDERING DATA

EXAMPLE: MCE48MW-LED32DMV40

MCE	48	MW	LED	Wattage and Lumen		Driver	Color Temp
Series	Size	Finish	Gear				
MCE	48 48 inches	MW Matte White Acrylic	LED				
				9.75" x 48"			
				32	32 Watts 3450 Lumens	MV Multi-volt 120V-277V	30 3000K
				48	48 Watts 4800 Lumens	DMV 0-10V Dimming	35 3500K
				57	57 Watts 5400 Lumens		40 4000K
				13.75" x 48"			50 5000K
				72	72 Watts 7000 Lumens		
				97	97 Watts 9600 Lumens		
				114	114 Watts 1080 Lumens		

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#	
JOB NAME	TYPE