

APPLICATIONS

Premium grade, designer, shallow, surface mounted wraparound luminaire. For use in indoor application where aesthetics and quality are important, such as kitchens, recreation rooms, nursing homes, retail stores and office areas. Regressed housing provides a floating appearance.

SIZE:

9.75"W x 50.0"L x 3.375"H

13.75"W x 50.0"L x 3.375"H



FEATURES & BENEFITS

- ◆ Every fixture is individually tested
- ◆ ETL_{us} Listed

SPECIFICATIONS

Die formed and spot welded, 22 gauge cold rolled steel housing. Spot welded for rigidity and clean appearance. Diffuser hinges from either side in a lift and shift manner and is self centering.

Mounting: Mounts over electrical junction box. Offset mounting pads which keeps luminaire level and slightly off of mounting surface, are formed within the housing. Mounting holes are provided within offset to prevent distortion of housing when tightening mounting fasteners.

Diffuser: Specially formed plastic diffuser produces flawless light source with even illumination on all sides and no distracting spots. Invisible hanging clips permit removal of lens from either side

ORDERING DATA

EXAMPLE: MCE48MW-LED32DMV40

MCE	48	MW	LED	Wattage and Lumen		Driver	Color Temp
Series	Size	Finish	Gear				
MCE	48 48 inches	MW Matte White Acrylic	LED	9.75" x 48" 32 32 Watts 3450 Lumens 48 48 Watts 4800 Lumens 57 57 Watts 5400 Lumens H67 67 Watts 6400 Lumens 13.75" x 48" 32 32 Watts 3450 Lumens 48 48 Watts 4800 Lumens 57 57 Watts 5400 Lumens H67 67 Watts 6400 Lumens		DMV 120-277V Multivolt 0-10V Dimmable Step dimming SDMV Multivolt DHV 347-480VAC 0-10V Dimming D347V 347VAC 0-10V Dimming TDMV Triac Dimming 120-277VAC D120 Triac Dimming 120VAC D277 Triac Dimming 277VAC	30 3000K 35 3500K 40 4000K 50 5000K

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#	
JOB NAME	TYPE