

**APPLICATIONS**

This compact, yet durable die-cast aluminum flood light provides a flood of light from a single LED diode. Lightings Facts approved to provide 2200 lumens and 50,000 hours of life using 24 watts. It is an ideal replacement for a 50W HID. Die-cast swivel arm 1/2" NPS makes mounting simple to a standard junction box. White reflector and tempered glass lens ensures performance and suitable for wet location. Ideal applications for security, building facades, displays, uplighting and signs. Good for lower level lighting in storage areas and commercial sites.



**FEATURES & BENEFITS**

- ◆ Aluminum die-cast housing
- ◆ Durable polyester powder coat finish
- ◆ Tempered glass lens
- ◆ Integrated heat fins for optimized heat dissipation
- ◆ White reflector
- ◆ 1/2" NPS die-cast swivel arm
- ◆ UL/cUL Listed for wet locations
- ◆ 5 year limited warranty

**SPECIFICATIONS**

Sturdy die-cast housing and face frame, powder coat finish with integrated heat fins for optimized heat dissipation. Minimum starting temperature -22°F, input voltage 120-277V 50/60Hz non-dimmable.

**ORDERING DATA**

**EXAMPLE: MFLS45LED20MV40BZ**

MFLS45						
Series	Gear	Wattage & Lumens		Driver	Color Temperature	Housing Color
MFLS45	LED	24	24 Watts 2200 Lumens	E120 Electronic 120v	40 4000K	BZ Bronze

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆  
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#			
JOB NAME		TYPE	