

**APPLICATIONS**

This compact, yet durable die-cast aluminum flood light provides a flood of light from a single LED diode. Lightings Facts approved to provide 2700 lumens and 50,000 hours of life using 30 watts. It is an ideal replacement for a 100W HID. Die-cast swivel are 1/2" NPS makes mounting simple to a standard junction box. White reflector and tempered glass lens ensures performance and suitable for wet location. Ideal applications for security, building facades, displays, uplighting and signs. Good for lower level lighting in storage areas and commercial sites.

**FEATURES & BENEFITS**

- ◆ Aluminum die-cast housing
- ◆ Durable polyester powder coat finish
- ◆ Tempered glass lens
- ◆ Integrated heat fins for optimized heat dissipation
- ◆ White reflector
- ◆ 1/2" NPS die-cast swivel arm
- ◆ LED, Citizen CLL032-1208
- ◆ System power 30W
- ◆ UL/cUL Listed for wet locations
- ◆ 5 year limited warranty
- ◆ Dimensions: 7.75"W x 5.75"H x 6.5"Ext




**SPECIFICATIONS**

Sturdy die-cast housing and face frame, powder coat finish with integrated heat fins for optimized heat dissipation. Minimum starting temperature -22°F, input voltage 120-277V 50/60Hz non-dimmable.

**ORDERING DATA**

**EXAMPLE: MFLS57LED30MV40BZ**



Dimensions and specifications subject to change without notice.

CAT#			
JOB NAME		TYPE	