

FEATURES & BENEFITS

- ◆ Dimmable 120V input voltage, 50/60Hz
- ◆ Ambient operating temperature -40°C (-40°F) to +50°C (122°F)
- ◆ Estimated 50,000 Hrs L₇₀
- ◆ Molded of durable non-corrosive UV resistant resins
- ◆ Acrylic diffuser
- ◆ Post tops fit most 3 inch diameter posts (not included)
- ◆ UL Listed for wet locations
- ◆ Energy Star Listed in wall and long tail versions



ORDERING DATA

EXAMPLE: MHTP-LED12D120WH30

MHT	LED	12	D120					
Series	Mount	Gear	Wattage / Lumens	Driver	Finish	Lens	Color Temp	Options
MHT	P Post Top W Wall Mount L Wall Mount Long Tail S Wall Mount Short Tail	LED	12 13 Watts 1000 Lumens Estimated from LED Source	D120 120VAC Triac Dimmable	WH White BK Black	C Clear Lens	30 3000K 40 4000K	PC Photocell* *Photocell Not Available on Post Top

ORDERING DATA FOR LED A LAMP


EXAMPLE: MHTWINCLEDWHC40

MHT							
Series	Socket	Lamp Type (Optional) ¹	Finish	Lens	Color Temp (Optional) ²	Options	
MHT	INC Incandescent	LED 9.5 watt A19/E26 120VAC 800 Lamp Lumens Triac Dimmable	WH White BK Black	C Clear Lens	30 3000K 40 4000K	PC Photocell ³ ³ Photocell Not Available on Post Top	
Mount		¹ Must include color temperature			² Must include LED Lamp Type		
P Post Top W Wall Mount L Wall Mount Long Tail S Wall Mount Short Tail							


Dimensions and specifications subject to change without notice.

DIMENSIONS


MHTW




MHTL



MHTS



MHTP



Dimensions and specifications subject to change without notice.