

FEATURES & BENEFITS

- ◆ Seamless fixture housing, die cast aluminum
- ◆ Hinged door frame, die cast aluminum
- ◆ Clear lens, heat and impact resistant tempered glass
- ◆ Segmented optics
- ◆ Durable powder coat finish. Standard colors: black or white. Custom colors available
- ◆ ETL Listed for wet locations

STANDARD FLOOD

Three Sizes: 12" x 12" x 6.25",
16" x 16" x 6.75", 22" x 22" x 9.25"

EPA Ratings

12" Housing 0° Tilt - EPA: .55
12" Housing 20° Tilt - EPA: .77
12" Housing 60° Tilt - EPA: 1.07
16" Housing 0° Tilt - EPA: .95
16" Housing 20° Tilt - EPA: 1.27
16" Housing 60° Tilt - EPA: 1.78
22" Housing 0° Tilt - EPA: 1.64
22" Housing 20° Tilt - EPA: 2.34
22" Housing 60° Tilt - EPA: 3.26



| Standard Flood Order Information | | |
|----------------------------------|-------------------|---------------------|
| Size | Catalog # | Wattage |
| 12" | MISMFLT50HPS | 50W-HPS-120-NPF |
| 12" | MISMFLT70HPS | 70W-HPS-120-NPF |
| 12" | MISMFLT100HPS | 100W-HPS-120-NPF |
| 12" | MISMFLT150HPS | 150W-HPS-120-NPF |
| 12" | MISMFLT150HPSQV | 150W-HPS-QV-CWA |
| 12" | MISMFLT150HPS480 | 150W-HPS-480-CWA |
| 12" | MISMFLT50MHQV | 50W-MH-PS-QV-SCWA |
| 12" | MISMFLT70MHQV | 70W-MH-PS-QV-SCWA |
| 12" | MISMFLT100MHQV | 100W-MH-PS-QV-SCWA |
| 12" | MISMFLT175HQV | 175W-MH-PS-QV-SCWA |
| 12" | MISMFLT175MH480 | 175W-MH-PS-480-SCWA |
| 16" | MIMDFLT150HPSQV | 150W-HPS-QV-CWA |
| 16" | MIMDFLT150HPS480 | 150W-HPS-480-CWA |
| 16" | MIMDFLT250HPSQV | 250W-HPS-QV-CWA |
| 16" | MIMDFLT250HP480 | 250W-HPS-480-CWA |
| 16" | MIMDFLT400HPSQV | 400W-HPS-QV-CWA |
| 16" | MIMDFLT400HPS480 | 400W-HPS-480-CWA |
| 16" | MIMDFLT175MHQV | 175W-MH-PS-QV-SCWA |
| 16" | MIMDFLT175MH480 | 175W-MH-PS-480-SCWA |
| 16" | MIMDFLT250MHQV | 250W-MH-PS-QV-SCWA |
| 16" | MIMDFLT250MH480 | 250W-MH-PS-480-SCWA |
| 16" | MIMDFLT400MHPSQV | 400W-MH-PS-QV-SCWA |
| 16" | MIMDFLT400MHPS480 | 400W-MH-PS-480-SCWA |
| 22" | MILGFLT400MHPSQV | 400W-MH-PS-QV |
| 22" | MILGFLT1000HPSQV | 1000W-HPS-QV-CWA |
| 22" | MILGFLT1000HPS480 | 1000W-HPS-480-CWA |
| 22" | MILGFLT1000MHQV | 1000W-MH-QV-CWA |
| 22" | MILGFLT1000MH480 | 1000W-MH-480-CWA |

*ARM FITTING SPECIFICATIONS

12" & 16" Housing requires MIPMV for multiple units placed at 90°
22" Housing requires MIPMVS18 for multiple units placed at 90°
For dual units placed at 180° parallel to building requires MIPMVS18.

Other housing and arm configurations are available. Please contact your Mobern Lighting Sales Representative for more information.

Dimensions and specifications subject to change without notice.

