

APPLICATIONS

Commercial grade shallow surface mounted vandal resistant LED fixture. For use in high abuse indoor applications such as schools and public buildings and any area where security is the primary consideration.

FEATURES & BENEFITS

- ◆ The ultimate in vandal resistant enclosed security fixtures
- ◆ Virtually indestructible UV stabilized lens is .177" clear polycarbonate
- ◆ Lens has a pyramidal prism design on bottom and vertical perimeter rib for maximum light control and efficiency
- ◆ Available in lengths from 24 to 48 inches - (2', 4' lengths)
- ◆ Fully gasketed to provide protection against dust, dirt, insects, moisture and other foreign dust particles
- ◆ Tamperproof screws are standard
- ◆ Every fixture individually tested
- ◆ ETL_{us} listed



SPECIFICATIONS

Housing is die-formed 20 gauge cold rolled steel. Finish is high reflectance baked white enamel. Injection molded, thick walled, clear prismatic diffuser is manufactured from high impact UV treated polycarbonate. Diffuser is held in place and secured with tamperproof stainless steel screws. Mounts over electrical junction box. Mounting holes are provided.

ORDERING DATA

EXAMPLE: SVP 48LED48DMV40

SVP		LED		Wattage / Lumens		Driver*		Color Temp		
Series	Width	Length		Gear						
SVP Surface Vandal Proof	Blank	9.5"	24	LED	2 Ft (Wide Only)		DMV	120-277VAC 0-10V Dimmable *Consult for Traic and Step Dimming Options	30	3000K
	N	4.8" (48 length only)	27" Nominal (not available in N width)		20	20 Watts			2000 Lumens	35
			48		24	24 Watts	2400 Lumens	40	4000K	
					28	28 Watts	2800 Lumens	50	5000K	
					30	30 Watts	3000 Lumens			
					4ft					
					23	23 Watts	3160 Lumens			
					28	28 Watts	2980 Lumens			
					35	35 Watts	4500 Lumens			
					48	48 Watts	5570 Lumens			
					57	57 Watts	6790 Lumens			
					72	72 Watts	7200 Lumens			
					4ft Narrow					
					15	15 Watts	1650 Lumens			
					20	20 Watts	2200 Lumens			
					24	24 Watts	2400 Lumens			
					28	28 Watts	2800 Lumens			
					30	30 Watts	3000 Lumens			

Lumens are approximate at 4000K 25 °C and subject to a tolerance ±10%

Wattage is approximate and subject to a tolerance of ±5% and is subject to environmental factors

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆
8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE

