

APPLICATIONS

Low bay areas that require a smaller LED enclosure

FEATURES & BENEFITS

- ◆ Compact size 26.6"L x 14.5"W x 5.8"H
- ◆ Poured in place gasket and latches seal the enclosure from hostile environments
- ◆ Very tough diffusers resist breakage and reduce replacement costs



End View



ORDERING DATA

EXAMPLE: VWHBS LED 80 FR DMV 30

VWHBS		LED											
Series	Gear	Mounting		Wattage & Lumens ¹		Diffuser Options		Driver ²		Color Temp		Options	
VWHBS	LED	Blank P	Standard Pendant/Conduit Single point 3/4" Hub	80	80 Watts 8000 Lumen	Blank FR PC	Clear Acrylic Frosted Acrylic Clear Polycarbonate	DMV	120-277V 0-10V Dimmable	30	3000K	CS EM OS OSW	6' Cord, 3 Wire 10W Emergency Occupancy sensor Occupancy sensor, wet located
				100	100 Watts 10,000 Lumen					35	3500K	PC	Photocell
				140	140 Watts 14,000 Lumen					40	4000K	SM	Stainless Mounting Strap
										50	5000K		

Notes:


¹ Consult for custom wattage and lumen packages.

² Consult for other driver options
(Step dimming, Triac dimming)

ACCESSORIES


- H137 V-Hook
VWFHB-MBCM Flexible Ceiling Mount

Surface Mount



Surface Mount fixture 1.25" from ceiling (VWFHB MBCM sold separately)

Pendant Mount



V Hook (H137) sold individually (need 2 per fixture)

REPLACEMENT PARTS

- H203 Stainless Mounting Strap
H199 Zinc Plated Mounting Strap



Accessory available for 3/4" Hub for single point mounting



Stainless hardware for mounting straps and latches

Dimensions and specifications subject to change without notice.

