

APPLICATIONS

Low bay areas that require a smaller LED enclosure

FEATURES & BENEFITS

- ◆ Compact size 26.6"L x 14.5"W x 5.8"H
- ◆ Poured in place gasket and latches seal the enclosure from hostile environments
- ◆ Very tough diffusers resist breakage and reduce replacement costs



End View

ORDERING DATA

EXAMPLE: VWHBS LED 80 FR DMV 30

Series	Gear	Mounting	Wattage & Lumens ¹	Diffuser Options	Driver ²	Color Temp	Options
VWHBS	LED	Blank Standard Pendant/Conduit Single point 3/4" Hub	80 80 Watts 8000 Lumen 100 100 Watts 10,000 Lumen 140 140 Watts 14,000 Lumen	Blank FR PC	DMV 120-277V 0-10V Dimmable	30 3000K 35 3500K 40 4000K 50 5000K	CS 6' Cord, 3 Wire EM 10W Emergency OS Occupancy sensor OSW Occupancy sensor, wet located PC Photocell SM Stainless Mounting Strap


*Cord & Whip Ordering Chart (Add to End of Fixture Part Number)						
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip	(Blank) 3 Wire	(Blank) 6 feet	(Blank) No Plug	BK - Black	(Blank) 120-277V	15 - 15 Amps
CS - Cordset	4 - 4 Wire	8 - 8 feet	P* - Standard Plug	WH - White	120 - 120V	20 - 20 Amps
	5 - 5 Wire	10 - 10 feet	TL* - Twist Lock		277 - 277V	
	6 - 6 Wire	12 - 12 feet			347 - 347V	
		15 - 15 feet			480 - 480V	

Notes:
¹ Consult for custom wattage and lumen packages.
² Consult for other driver options (Step dimming, Triac dimming)
 *See chart for whip and cordset options

ACCESSORIES


H137 V-Hook
 VWFHB-MBCM Flexible Ceiling Mount

Surface Mount



Surface Mount fixture 1.25" from ceiling (VWFHB MBCM sold separately)

Pendant Mount



V Hook (H137) sold individually (need 2 per fixture)

REPLACEMENT PARTS

H203 Stainless Mounting Strap
 H199 Zinc Plated Mounting Strap



Accessory available for 3/4" Hub for single point mounting



Stainless hardware for mounting straps and latches

Dimensions and specifications subject to change without notice.

