



L I G H T I N G

Professional Series

VWN PLED LED Narrow Vaportight Fixture

APPLICATIONS

Introducing the Mobern VWN-LED Premium grade enclosed and gasketed vaportight fixture. This Energy-Saving High Performance LED Vaportight is ideal for both indoor and outdoor applications where dust and water resistance is required. Ideal for parking garages, cold storage, marinas, barns, canopies, car washes, poultry farms, agricultural applications and other areas susceptible to corrosive and wet conditions.

FEATURES & BENEFITS

- ◆ Designed for easy assembly
- ◆ Ease of Installation and Maintenance
- ◆ Visually familiar light sourcing
- ◆ Poured in place gasket seals the enclosures from most hostile environments
- ◆ Economical Mounting System can provide dramatic savings on installation labor, thus reducing costs
- ◆ Very tough diffusers resist breakage and reduce replacement and maintenance costs
- ◆ Available in 4' length only
- ◆ Frosted lens for reducing direct glare and image of the LED
- ◆ Optional durable stainless steel mounting hardware
- ◆ No need to drill through the housing for installation
- ◆ Optional stainless steel bail for chain/cable hung installations
- ◆ Consult for other options



SPECIFICATIONS

High quality enclosed fiberglass fixture features a unique continuous poured gasket which completely fills channel for maximum seal integrity. Diffuser is held in place with POM retaining latches. Stainless steel latches are recommended for the following applications: agriculture, car washes, food processing and swimming pools. Hole is 7/8" diameter and is provided with a plastic plug on one end for conduit attachment. Offset mounting pads which keeps luminaire level and slightly off of mounting surface are formed within the housing. Standard diffuser is high impact acrylic with textured pattern designed for high efficiency while providing reduced glare.

ORDERING DATA

EXAMPLE: VWN4P-LED34DMVSC40

VWN		P		LED		Driver		Lens		Color Temp		Options						
Series	Length	Suffix	Gear	Wattage/Lumens														
VWN LED Vaportight	4 4 ft	P (Professional Series)	LED	34 34 Watts 4100 Lumens	MV 120-277 VAC Multivolt	DMV 120-277VAC 0-10V Dimmable	Blank High Impact Acrylic P Polycarbonate	SC Smooth Clear	SF Smooth Frosted	RC Ribbed Clear	RF Ribbed Frosted	30 3000K	35 3500K	40 4000K	50 5000K	CS Cord 18/3 6"	OS Occupancy Sensor	OSW Occupancy Sensor - Wet Location

DLC Listed Models

VWN4P-LED34MVSFxx xx = 30,35,40,50




DIMENSIONS


Housing Only



RC/RF Lens



End View



Lumens are subject to a tolerance $\pm 10\%$
Wattage is approximate and subject to a tolerance of $\pm 5\%$
Dimensions and specifications subject to change without notice.



800-444-WATT ♦ www.mobern.com ♦

8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE