



**JOB NAME:**

**CAT#:**

**TYPE:**

## APPLICATIONS

This unique LED Retrofit Kits is an energy efficient, easy to install solution to upgrade your fluorescent troffer to LED. Compatible with both standard and narrow T-grids, it offers a simple retrofit that will improve the look of your ceiling with its architectural styling without the need to actually break the ceiling plenum. This kit offers a true Indirect/Direct solution that not only provides more energy efficiency but also the true comfortable performance of an indirect/direct fixture designed especially for workspaces with CRTs. The main diffuser and slanted troffer help reduce glare and create a pleasant, uniform throw of light. With this kit, you will get the energy savings and performance of the latest technology without the fuss and mess of changing out fixtures completely.

The RKDISE retrofit kit is a great upgrade solution for converting fluorescent troffers to LED. The kit provides a stylish architectural look without breaking the ceiling plenum, and provides a more efficient solution with greater energy savings and the performance of the latest technology without the fuss and mess of changing out complete fixtures.



## FEATURES & BENEFITS

- Input voltage 120-277VAC
- cETL<sub>US</sub> recognized as retrofit
- 0-10V Dimmable
- 5 year warranty
- THD <10%
- PF >0.95
- Min CRI 82

## DIMENSIONS

**1x4** - 48.0"L x 12.0"W x 3.65"H

**2x2** - 23.97"L x 23.97"W x 3.65"H

**2x4** - 48.0"L x 23.97"W x 3.65"H

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

**ORDERING**

EXAMPLE: RKDISE 14 LED 17 DMV FR 30 SS

RKDISE		LED										
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS		5. DRIVER		6. LENS		7. COLOR TEMP		8. EMERGENCY (O) <sup>1</sup>	
RKDISE	<b>14</b> 1X4	<b>LED</b>	<b>1x4 Standard</b>		<b>DMV</b>	120-277V Multivolt 0-10V Dimmable	<b>FR</b>	Frosted	<b>30</b>	3000K	<b>EM</b>	Emergency Battery Backup
	<b>22</b> 2X2		<b>17</b>	17 Watts 2260 Lumens				<b>35</b>	3500K			
	<b>24</b> 2X4		<b>22</b>	22 Watts 2295 Lumens	<b>SDMV</b>	Step dimming multivolt		<b>40</b>	4000K			
			<b>24</b>	24 Watts 3260 Lumens				<b>50</b>	5000K			
			<b>30</b>	30 Watts 4140 Lumens								
			<b>32</b>	32 Watts 4435 Lumens								
			<b>35</b>	35 Watts 4725 Lumens								
			<b>40</b>	40 Watts 5235 Lumens								
			<b>45</b>	45 Watts 5770 Lumens								
			<b>50</b>	50 Watts 6280 Lumens								
			<b>2X2 Standard</b>									
			<b>17</b>	17 Watts 2260 Lumens								
			<b>18</b>	18 Watts 2410 Lumens								
			<b>20</b>	20 Watts 2880 Lumens								
			<b>24</b>	24 Watts 3125 Lumens								
			<b>28</b>	28 Watts 3610 Lumens								
			<b>30</b>	30 Watts 3775 Lumens								
			<b>35</b>	35 Watts 4160 Lumens								
			<b>40</b>	40 Watts 5160 Lumens								
			<b>45</b>	45 Watts 5780 Lumens								
			<b>2X4 Standard</b>									
			<b>15</b>	15 Watts 2155 Lumens								
			<b>21</b>	21 Watts 3090 Lumens								
			<b>28</b>	28 Watts 4060 Lumens								
			<b>30</b>	30 Watts 4315 Lumens								
			<b>32</b>	32 Watts 4600 Lumens								
			<b>35</b>	35 Watts 5030 Lumens								
			<b>40</b>	40 Watts 5700 Lumens								
			<b>48</b>	48 Watts 6690 Lumens								
			<b>57</b>	57 Watts 7675 Lumens								

**9. SENSOR (O)<sup>1</sup>**

- SS** Integrated Sensor
- SNS200** Occupancy Sensor w/ daylight harvesting

**Notes:**

<sup>1</sup>(O) is optional

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

**DLC INFORMATION**



DLC Listed Models 2x4	
RKDISE24-LED21FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED28FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED30FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED32FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED35FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED40FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED48FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE24-LED57FRDMVxx	xx = Color Temp 30, 35, 40, 50

DLC Listed Models 2x2	
RKDISE22-LED17FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED18FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED20FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED24FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED28FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED30FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED31FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED35FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED40FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE22-LED45FRDMVxx	xx = Color Temp 30, 35, 40, 50

DLC Listed Models 1x4	
RKDISE14-LED17FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED22FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED24FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED30FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED32FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED35FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED40FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED45FRDMVxx	xx = Color Temp 30, 35, 40, 50
RKDISE14-LED50FRDMVxx	xx = Color Temp 30, 35, 40, 50

Dimensions and specifications subject to change without notice.

