



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Premium grade recessed deep cell parabolic T-bar troffer designed for maximum efficiency and visual comfort. Ideal for commercial and industrial buildings requiring general illumination with recessed configurations and low glare.

- P3 Technology - Post Powder Paint
- >90% reflectivity
- Corrosion and scratch resistant
- Smooth edges for easy handling
- Louver manufactured from low iridescent semi-specular anodized aluminum
- Protective plastic dust cover keeps louver clean during shipping and installation
- Black reveal provides gap free floating louver appearance
- Hinges from either side
- Die-formed steel T-hinges
- Positive locking cam action latches
- Air functions - choice of static air supply or heat removal
- Various cell configurations available
- Access plate for quick wiring
- Equipped with Integral Earthquake Clips
- Every fixture individually tested
- UL listed for damp location

Housing and ends are die-formed from cold rolled steel. Body and the black reveal are highly reflective P3 - Post Powder Paint. Precision formed anodized semi-specular aluminum louver. Standard normal 3" deep cell louvers are manufactured using interlocked construction and mitred corners. Wiring access plate or knockouts are provided on back of housing for flexible conduit attachment. Listed by and bears UL label.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

DIMENSIONS

- 2ft - 6" x 24" x 6"
- 4ft - 6" x 48" x 6"
- 8ft - 6" x 96" x 6"



Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.mobern.com/EZLEDemergency.

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: RP 14 2 17 LEDL7W 8 830 OL

RP

1. SERIES	2. SIZE	3. # OF LAMPS	4. LAMP TYPE	5. LAMP WATTAGE	6. LOUVERS
RP Recessed Parabolic	14 1X4	2 2 Lamps	17 24 inch T8	T8 OPTIONS <u>2 ft.</u> LEDL7W 7 Watts 950 Lumens <u>Keystone</u> LEDL9W 9 Watts 1050 Lumens <u>Lunera</u> LEDL9W 9 Watts 1050 Lumens <u>4 ft.</u> LEDL12W 12.5 Watts 1750 Lumens <u>Keystone</u> LEDL15W 15 Watts 1740 Lumens <u>Lunera</u> LEDL15W 15 Watts 1740 Lumens LEDL18W* 18 Watts 2500 Lumens T5 OPTIONS LEDL25W 25 Watts 3300 Lumens	1X4 8 8 cell (1x8 pattern) Semi-specular, 3 in. nominal 2X2 9 9 cell (3x3 pattern) Semi-specular, 3 in. nominal 12 12 cell (4x3 pattern) Semi-specular, 3 in. nominal 16 16 cell (4x4 pattern) Semi-specular, 3 in. nominal 2X4 12 12 cell (2x6 pattern) Semi-specular, 3 in. nominal 16 16 cell (2x8 pattern) Semi-specular, 3 in. nominal 18 18 cell (3x6 pattern) Semi-specular, 3 in. nominal 24 24 cell (4x6 pattern) Semi-specular, 3 in. nominal 32 32 cell (4x8 pattern) Semi-specular, 3 in. nominal
	22 2X2	3 3 Lamps	32 48 inch T8		
	24 2X4	4 4 Lamps	54 46 inch T5HO		

7. COLOR TEMP	8. LAMP BRAND	9. OVERLAY (O)'	10. WHIP (O)'	11. INVERTER (O)'
830 3000K	Blank House Brand	OL Frosted Overlay Behind Louver	WP 6" whip, 3 wire	INV5 5W Integrated Inverter
835 3500K	LUN Lunera			
840 4000K	KEY Keystone Brand			
850 5000K	JAM James Brand**			

** Special order

Notes:
'(O) is optional

Dimensions and specifications subject to change without notice.

